


Technical data sheet

Wiring trunking BE-DIN 75, trunking width 37.5

Item number: 6132382



Wiring trunking for horizontal and vertical routing in the switchgear cabinet. Direct mounting on the wall with double-sided adhesive tape or via the integrated base perforation. Flame-retardant and self-extinguishing after removal of an active flame. The retainers in the trunking base can be broken out without tools. Tested to DIN EN 50085-2-3. Base and cover in set.



PVC Polyvinylchloride

Master data

Item number	6132382
Type	BEDIN 7537 sgr
Description 1	Slotted cable trunking system
Description 2	BE DIN Set 75x37,5 7030
Manufacturer	OBO
Colour	Stone grey; RAL 7030
Material	Polyvinylchloride
Smallest sales unit	50
Unit of quantity	Metre
Weight	50.674 kg
Weight unit	kg/100 m

Dimensions

Length	2,000 mm
Width	33 mm
Height	75 mm

Technical data sheet

Wiring trunking BE-DIN 75, trunking width 37.5

Item number: 6132382



Technical data

Side wall version	Slotted
Fastening type	Base perforation
Flexible	no
Halogen-free	no
Creepage current-resistant	yes
With cover	yes
Usable cross-section	19.8 cm ²
Slot spacing	10 mm
Slot width	4 mm
Self-extinguishing	yes