

Technical data sheet

CL 60 device installation trunking, trunking width 165

Item number: 6132921



CLIDI NF device installation trunking for covered cable routing and device installation in internal areas.
Direct wall mounting using base perforation. Hardly inflammable and self-extinguishing after removal of a naked flame. Change the direction with the fittings and close the trunking ends with end pieces.



PVC Polyvinylchloride

Master data

Item number	6132921
Type	CL 16560 blc
Description 1	Device installation trunking
Description 2	CLIDI Set 60x165 9010
Manufacturer	OBO
Colour	Pure white; RAL 9010
Material	Polyvinylchloride
Smallest sales unit	12
Unit of quantity	Metre
Weight	168.4 kg
Weight unit	kg/100 m

Dimensions

Length	2,000 mm
Width	165 mm
Height	62 mm

Technical data sheet

CL 60 device installation trunking, trunking width 165

Item number: 6132921



Technical data

Number of covers	2
Number of insertable partitions	1
Rectangular shape	no
Halogen-free	no
Cable retaining clip	no
Duct connector	no
Cover mounting type	Internal
Mounting perforation in base	yes
Usable cross-section	7400 mm ²
Cover supplied	yes
Cover width	45 mm
Cover width 2	45 mm
Protection rating	IP40
Protection rating IK code	IK08
Symmetrical	no
Permitted temperature range, max.	60 °C
Permitted temperature range, min.	-5 °C