

# Technical data sheet

## CL 55 device installation trunking, trunking width 90

Item number: 6132911



CLIDI NF device installation trunking for covered cable routing and device installation in internal areas.  
Direct wall mounting using base perforation. Hardly inflammable and self-extinguishing after removal of a naked flame. Change the direction with the fittings and close the trunking ends with end pieces.



**PVC** Polyvinylchloride

### Master data

Item number	6132911
Type	CL 9055 blc
Description 1	Device installation trunking
Description 2	CLIDI Set 55x90 9010
Manufacturer	OBO
Colour	Pure white; RAL 9010
Material	Polyvinylchloride
Smallest sales unit	16
Unit of quantity	Metre
Weight	87 kg
Weight unit	kg/100 m

### Dimensions

Length	2,000 mm
Width	90 mm
Height	55 mm

# Technical data sheet

CL 55 device installation trunking, trunking width 90

Item number: 6132911



## Technical data

Number of covers	1
Number of insertable partitions	1
Rectangular shape	yes
Halogen-free	no
Cable retaining clip	no
Duct connector	no
Cover mounting type	Internal
Mounting perforation in base	yes
Usable cross-section	4230 mm <sup>2</sup>
Cover supplied	yes
Cover width	45 mm
Protection rating	IP40
Protective film	no
Protection rating IK code	IK08
Symmetrical	no
Permitted temperature range, max.	60 °C
Permitted temperature range, min.	-5 °C