

Technical data sheet

External corner CL AE 9055



Item number: 6132932

External corner as a fitting for changing the direction of the CLIDI NF device installation trunking.
Cut-concealing external corner for snapping onto the base.



ASA Acrylnitrile-styrene-acrylester

Master data

| | |
|---------------------|---------------------------------|
| Item number | 6132932 |
| Type | CL AE9055 blc |
| Description 1 | External corner |
| Description 2 | CLIDI 55x90 9010 var. |
| Manufacturer | OBO |
| Colour | Pure white; RAL 9010 |
| Material | Acrylnitrile-styrene-acrylester |
| Smallest sales unit | 1 |
| Unit of quantity | Piece |
| Weight | 8.5 kg |
| Weight unit | kg/100 pc. |

Dimensions

| | |
|--------|--------|
| Length | 110 mm |
| Width | 110 mm |
| Height | 98 mm |

Technical data sheet

External corner CL AE 9055



Item number: 6132932

Technical data

| | |
|-----------------------------------|--------------|
| Version for | Hood fitting |
| Halogen-free | no |
| Cable retaining clip | no |
| Duct connector | no |
| Cover mounting type | Internal |
| Mounting perforation in base | no |
| Cover width | 0 mm |
| Cover width 2 | 0 mm |
| Cover width 3 | 0 mm |
| Protection rating | IP40 |
| Protective film | no |
| Protection rating IK code | IK07. |
| Symmetrical | yes |
| Permitted temperature range, max. | 60 °C |
| Permitted temperature range, min. | -5 °C |
| Angle range, max. | 110 mm |
| Angle range, min. | 70 mm |